



Splittable Flying Splice Tape 7387

Product Data Sheet

August 2016
Supersedes: NEW

Product Description

A splittable tape construction designed for straight-line flying splices, furnished with aggressive adhesives on both sides and a coated paper liner with liner score for easy manual application.

Key Features

- designed for straight-line flying splices for a variety of film substrates such as polyethylene, cast polypropylene & aluminium foil.
- designed so that no fibres are present after splitting, thereby preventing contamination of the central impression drum and removing the need for costly cleaning to remove fiber residues after splicing.

Physical Properties

Adhesive Type Splicing side	Rubber adhesive	
Adhesive Type Reel side	Acrylic adhesive	
Tape Colour	White (splicing side) White (reel side) Blue elliptic pattern inside	
Carrier	Splicing side: Paper Reel side: Paper	
Thickness (ASTM D-3652)	Before splitting	After splitting
Tape	0.281 mm	Splice side 0.117 mm
Liner	0.056 mm	Reel side 0.118 mm
Total	0.337 mm	
Splittable Layer	Fiber-free cleavable layer	
Release Liner	Coated easy-release paper	

Physical Properties

Repulpability	Construction is not repulpable
Bonding Strength	Designed for high affinity to film substrates

Storage & Shelf Life

Store at 16 °C – 27 °C and 40 – 60 % Relative Humidity in its original carton.

The product can be stored up to 12 months after production.

It is recommended to remove the protective liner just prior to splicing, rather than leaving film rolls with prepared splice patterns in storage without the protective liner.

For Additional Information

To request additional product information or to arrange for sales assistance, please call your local sales representative.

Address correspondence to: 3M

Important Notice

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications.

This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

3M is a trademark of the 3M Company.



Insert Company Information Before Issue