

tesa® Masking Tape Excellent

Product Information

BNR 56548, 56546, 56549, 56547, 56556, 56555, 56545



Product Description

The tesa® Masking Tape Excellent is a good quality tape for indoor painting activities. The combination of great adhesive properties and the smooth backing guarantees sharp paint edges. It is hand-tearable, sticks well to a variety of surfaces and is easy to remove.

No traces are left behind, with great residue-free removal for up to 1 month indoors. Achieve good results with easy application with tesa® Masking Tape Excellent.

Product Features

- Ideal for good quality indoor masking tasks - achieve great results with indoor paint jobs
- Smooth flat paper backing guarantees sharp paint edges
- Residue-free removal for up to 1 month indoors
- Flexible: Adapts well to a variety of surfaces - finely plastered walls, wallpapers, glass, aluminium, hard-PVC and wood
- Suitable for all paints, lacquers and glazes
- Easy to use: tesa® Masking Tape Excellent is convenient and tear-resistant

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------|-------------------|--------|
| • Backing | flat paper | • Total thickness | 120 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|----------------------|---------|-----------------------------------|---------|
| • Tensile strength | 37 N/cm | • Batteries required | no |
| • Applicationfield | Home | • Hand tearability | yes |
| • Area of use | Indoor | • Residue-free removable after... | 30 days |
| • Batteries included | no | days | |
| | | • Tear resistance | yes |

tesa[®] Masking Tape Excellent

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.