

Technical Data				August, 2011	
Product Description	Scotch [®] High Temperature Fine Line Tape 4737 is a vinyl paint masking tape for fascia, rocker panels, two-tone and other multiple color applications where critical paint break lines are required.				
Product Construction	Backing	Adhesive	Color	Standard Roll Length	
	Vinyl	Rubber	Scotch [®] Tape 4737S - Blue (Solid) Scotch [®] Tape 4737T - Blue (Translucent)	36 yds. (32.9 m)	
lypical Physical Properties			ormation and data should be co not be used for specification pu	rposes.	
		10.5		ASTM Test Metho	
	Adhesion to Steel:		oz./in. width (11.5 N/100 mm)	D-3330	
	Tensile Strength:		s./in.width (280 N/100 mm)	D-3759	
	Elongation at Brea			D-3759	
	Tape Thickness: Temperature Use		0.300°F (149°C) for up to 30 minu	D-3652	
Features	up to 300°F (149°C) given application and temperature of the su it meets your needs.	for 30 minutes. The a l can vary due to subs rface at removal). We	el and found to leave little to no adhesive ctual temperature and time performance trate coatings and processing conditions suggest testing the product under your p esigned for uniform stretching	may be higher or lower for a (i.e. multiple bake cycles and th process conditions to determine i	
	paint lines.				
	• The adhesive and backing work together to minimize paint seepage.				
	• Outstanding fine line color separation.				
	• Smooth trimmed edges create a continuous straight paint line.				
	• Designed for indoor use.				
	• Vinyl backing is heat resistant for one piece removal.				
	• Functions with high temperature paint bake cycles.				
	• Minimal neck down when stretched for accurate paint lines.				
	• Scotch [®] Tape 4737S - Solid backing aids in seeing contrast with substrate color.				
	 Scotch[®] Tape 4737T – Translucent backing allows visual confirmation of adhesive wet out on substrate. 				
	-		C		

Scotch® High Temperature Fine Line Tape

4737S • 4737T

Application Ideas	Ideal for the transportation OEM industry for paint masking of metal and plastic surfaces.			
Storage	Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.			
Shelf Life	To obtain best performance, use this product within one year from date of manufacture.			
Technical Information	The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.			
Product Use	Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.			
Warranty, Limited Remedy, and Disclaimer	Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.			
Limitation of Liability	Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.			
	This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2008 standards			



Industrial Adhesives and Tapes Division 3M Center, Building 225-3S-06 St. Paul, MN 55144-1000 800-362-3550 • 877-369-2923 (Fax) www.3M.com/industrial



Scotch is a registered trademark of 3M. Printed in U.S.A. ©3M 2011 70070951036 (8/11)