MATERIAL SAFETY DATA SHEET 3130, 4130, 5130, 483, 481, 4811, 5421, 5423; Cold Seal® Polyethylene Tape 3130, 4130, 5130 & 25X130P / S69B, 3MTM Polyethylene Film Tape 483 (all colors), 3MTM Preservation Tape 481 & 4811, and 3MTM UHMW Film Tape 5421 & 5423 02/14/13



Material Safety Data Sheet

Copyright, 2013, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This material safety data sheet (MSDS) is provided as a courtesy in response to a customer request. This product is not regulated under, and a MSDS is not required for this product by the OSHA Hazard Communication Standard (29 CFR 1910.1200) because, when used as recommended or under ordinary conditions, it should not present a health and safety hazard. However, use or processing of the product not in accordance with the product's recommendations or not under ordinary conditions may affect the performance of the product and may present potential health and safety hazards.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3130, 4130, 5130, 483, 481, 4811, 5421, 5423; Cold Seal® Polyethylene Tape 3130, 4130,

5130 & 25X130P / S69B, 3MTM Polyethylene Film Tape 483 (all colors), 3MTM Preservation Tape 481 & 4811, and 3MTM UHMW Film Tape 5421 & 5423

MANUFACTURER:

DIVISION: Industrial Adhesives and Tapes Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 02/14/13 **Supercedes Date:** 12/01/10

Document Group: 26-9192-1

Product Use:

Specific Use: Protection Industrial use Intended Use:

Cold Seal® Polyethylene Tape 3130, 4130, 5130 & 25X130P / S69B

3MTM Polyethylene Film Tape 483 (all colors)

3MTM Preservation Tape 481 & 4811 3MTM UHMW Film Tape 5421 & 5423

SECTION 2: INGREDIENTS

Ingredient C.A.S. No. <u>% by Wt</u> Polyethylene Backing 51 - 99 None Natural Rubber Adhesive Trade Secret 1 - 49 Paper Liner (UHMW-PE Tapes Only) None Not Applicable MATERIAL SAFETY DATA SHEET 3130, 4130, 5130, 483, 481, 4811, 5421, 5423; Cold Seal® Polyethylene Tape 3130, 4130, 5130 & 25X130P / S69B, $3M^{TM}$ Polyethylene Film Tape 483 (all colors), $3M^{TM}$ Preservation Tape 481 & 4811, and $3M^{TM}$ UHMW Film Tape 5421 & 5423 - 02/14/13

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Odor, Color, Grade: various colored polyethylene tape

General Physical Form: Solid

Immediate health, physical, and environmental hazards: The environmental properties of this product present a low environmental hazard. This product, when used under reasonable conditions and in accordance with the 3M directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential health and safety hazards.

3.2 POTENTIAL HEALTH EFFECTS

Eve Contact:

No health effects are expected.

Skin Contact:

No health effects are expected.

Inhalation:

No health effects are expected.

Ingestion:

No health effects are expected.

3.3 POTENTIAL ENVIRONMENTAL EFFECTS

This substance does not leach metals or other RCRA (Resource Conservation and Recovery Act) listed TCLP (Toxic Characteristic Leaching Procedure) hazardous substances at concentrations that would make the product a hazardous waste.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact:
Skin Contact:
Inhalation:
If Swallowed:

No need for first aid is anticipated.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperatureNot ApplicableFlash PointNot ApplicableFlammable Limits(LEL)Not Applicable

MATERIAL SAFETY DATA SHEET 3130, 4130, 5130, 483, 481, 4811, 5421, 5423; Cold Seal® Polyethylene Tape 3130, 4130, 5130 & 25X130P / S69B, $3M^{TM}$ Polyethylene Film Tape 483 (all colors), $3M^{TM}$ Preservation Tape 481 & 4811, and $3M^{TM}$ UHMW Film Tape 5421 & 5423 - 02/14/13

Flammable Limits(UEL)

Not Applicable

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: No unusual fire or explosion hazards are anticipated.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Not applicable.

6.2. Environmental precautions

Not applicable.

Clean-up methods

Not applicable.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions.

7.2 STORAGE

Not applicable.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Not applicable.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact.

8.2.2 Skin Protection

Avoid prolonged or repeated skin contact.

MATERIAL SAFETY DATA SHEET 3130, 4130, 5130, 483, 481, 4811, 5421, 5423; Cold Seal® Polyethylene Tape 3130, 4130, 5130 & 25X130P / S69B, 3MTM Polyethylene Film Tape 483 (all colors), 3MTM Preservation Tape 481 & 4811, and 3MTM UHMW Film Tape 5421 & 5423 02/14/13

8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

8.2.4 Prevention of Swallowing

Not an expected route of exposure.

8.3 EXPOSURE GUIDELINES

None Established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Odor, Color, Grade: various colored polyethylene tape

General Physical Form: Solid

Autoignition temperature Not Applicable **Flash Point** Not Applicable Flammable Limits(LEL) Not Applicable Not Applicable Flammable Limits(UEL) **Boiling Point** Not Applicable **Density** Not Applicable **Vapor Density** Not Applicable

Vapor Pressure Not Applicable

Specific Gravity Not Applicable Not Applicable pН Not Applicable **Melting point**

Solubility in Water

Evaporation rate Not Applicable **Volatile Organic Compounds** Not Applicable Kow - Oct/Water partition coef Not Applicable Not Applicable Percent volatile **VOC Less H2O & Exempt Solvents** Not Applicable Viscosity Not Applicable

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

None known

10.2 Materials to avoid

None known

MATERIAL SAFETY DATA SHEET 3130, 4130, 5130, 483, 481, 4811, 5421, 5423; Cold Seal® Polyethylene Tape 3130, 4130, 5130 & 25X130P / S69B, $3M^{TM}$ Polyethylene Film Tape 483 (all colors), $3M^{TM}$ Preservation Tape 481 & 4811, and $3M^{TM}$ UHMW Film Tape 5421 & 5423 02/14/13

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

SubstanceConditionHydrocarbonsDuring CombustionCarbon monoxideDuring CombustionCarbon dioxideDuring Combustion

Hazardous Decomposition: Under recommended usage conditions, hazardous decomposition products are not expected. Hazardous decomposition products may occur as a result of oxidation, heating, or reaction with another material.

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Reclaim if feasible. If product can't be reclaimed, dispose of waste product in a sanitary landfill. Alternatively, incinerate the waste product in an industrial, commercial, or municipal incinerator.

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

Not regulated per U.S. DOT, IATA or IMO.

MATERIAL SAFETY DATA SHEET 3130, 4130, 5130, 483, 481, 4811, 5421, 5423; Cold Seal® Polyethylene Tape 3130, 4130, 5130 & 25X130P / S69B, $3M^{TM}$ Polyethylene Film Tape 483 (all colors), $3M^{TM}$ Preservation Tape 481 & 4811, and $3M^{TM}$ UHMW Film Tape 5421 & 5423 - 02/14/13

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and <u>not</u> the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 0 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Section 1: Product name was modified.

Section 1: Product use information was modified.

Section 16: Disclaimer (second paragraph) was modified.

Section 10: Hazardous decomposition or by-products table was modified.

Section 14: Transportation legal text was modified.

Page Heading: Product name was modified.

Section 9: Density information was modified.

Section 9: Vapor density value was modified.

Section 9: Vapor pressure value was modified.

Section 9: Boiling point information was modified.

MATERIAL SAFETY DATA SHEET 3130, 4130, 5130, 483, 481, 4811, 5421, 5423; Cold Seal® Polyethylene Tape 3130, 4130, 5130 & 25X130P / S69B, 3MTM Polyethylene Film Tape 483 (all colors), 3MTM Preservation Tape 481 & 4811, and 3MTM UHMW Film Tape 5421 & 5423 02/14/13

Section 5: Flammable limits (UE) information was modified.

Section 5: Flammable limits (LEL) information was modified.

Section 5: Autoignition temperature information was modified.

Section 5: Flash point information was modified.

Section 9: Property description for optional properties was modified.

Section 9: Specific gravity information was modified.

Section 9: pH information was modified.

Section 9: Melting point information was modified.

Section 9: Solubility in water text was modified.

Section 9: Flash point information was modified.

Section 9: Flammable limits (LEL) information was modified.

Section 9: Flammable limits (UEL) information was modified.

Section 9: Autoignition temperature information was modified.

Section 2: Product identification comment was modified.

Section 2: Ingredient table was modified.

Section 6: 6.2. Environmental precautions heading was modified.

Section 6: 6.1. Personal precautions, protective equipment and emergency procedures heading was modified.

Section 16: Web address was added.

Section 1: Address was added.

Copyright was added.

Company logo was added.

Telephone header was added.

Company Telephone was added.

Section 1: Emergency phone information was added.

Section 1: Emergency phone information was deleted.

Company Logo was deleted.

Copyright was deleted.

Section 16: Web address heading was deleted.

Section 1: Address line 1 was deleted.

Section 1: Address line 2 was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com